

Non-Rated & Rated Wood Jambs, Sills & Astragals





TABLE OF CONTENTS

Clear Poplar Primed Double Rabbet Jambs	, Flat	Jambs	&	Stops	/	Fire	Ro	ıted	J	an	nbs	ì	2
Hardwood Jambs & Additional Services													. 3
Pine Jambs													. 4
Astragals & Composite Jambs													. 5
Wood Thresholds, Saddles & Sills													. 6
Captiva Fire Rated Door Core													. 7
Cantiva Fire Rated Doors & Frames													۶



CLEAR POPLAR PRIMED JAMBS


POPLAR DOUBLE RABBETT JAMB PRIMED

THICKNESS x WIDTH x LENGTH	DOOR THICKNESS	PAIR *
1-1/4" x 4-11/16" x 7'4"	1-3/8" / 1-3/4"	STOCK
1-1/4" x 4-11/16" x 9'4"	1-3/8" / 1-3/4"	sтоск
1-1/4" x 4-7/8" x 7'4"	1-3/8" / 1-3/4"	STOCK
1-1/4" x 4-7/8" x 9'4"	1-3/8" / 1-3/4"	sтоск
1-1/4" x 6-11/16" x 7'4"	1-3/8" / 1-3/4"	sтоск
1-1/4" x 6-11/16" x 9'4"	1-3/8" / 1-3/4"	STOCK



POPLAR FLAT JAMB PRIMED

THICKNESS x WIDTH x LENGTH	DOOR THICKNESS	PAIR *
3/4" x 4-7/8" x 7'4"	1-3/8" / 1-3/4"	STOCK
3/4" x 4-7/8" x 9'4"	1-3/8" / 1-3/4"	sтоск
3/4" x 6-7/8" x 7'4"	1-3/8" / 1-3/4"	sтоск
3/4" x 6-7/8" x 9'4"	1-3/8" / 1-3/4"	sтоск



POPLAR STOPS PRIMED

(2-1/2 pieces per 3/0 door, 3 pieces for 6/0 door)

THICKNESS x WIDTH x LENGTH	ITEM	EACH
1/2" x 1-1/8" x 8'3"	WM888PP	STOCK
1/2" x 1-1/8" x 8'3"	WM936PP	STOCK



MADE TO ORDER ALLOW 5 - 7 DAYS PRODUCTION. OTHER WOOD

SPECIES & PROFILES AVAILABLE.

FIRE RATED PRIMED POPLAR

20, 45, 60, 90 Minute Ratings Available

DOUBLE RABBETT JAMBS

THICKNESS x WIDTH x LENGTH	DOOR THICKNESS	UP TO 4' x 8' SET	4'1 TO 8' WIDTH UP TO 8' HEIGHT SET	
1-1/4" x 4-7/8"				
20 MIN. NEUTRAL PRESSURE	1-3/4"			
20 MIN. POSITIVE PRESSURE	1-3/4"			
45 MIN. POSITIVE PRESSURE	1-3/4"	CALL FOR PRICING	CALL FOR PRICING	
60 MIN. POSITIVE PRESSURE	1-3/4"			
90 MIN. POSITIVE PRESSURE	1-3/4"			
1-1/4" x 6-3/4"				
20 MIN. NEUTRAL PRESSURE	1-3/4"			
20 MIN. POSITIVE PRESSURE	1-3/4"			
45 MIN. POSITIVE PRESSURE	1-3/4"	CALL FOR PRICING	CALL FOR PRICING	
60 MIN. POSITIVE PRESSURE	1-3/4"			
90 MIN. POSITIVE PRESSURE	1-3/4"			



ALL WOOD SPECIES AVAILABLE. CALL FOR PRICING.

SEE CAPTIVA FIRE SPECS PAGE 7-8



HARDWOOD JAMBS

(AVAILABLE IN ALL SPECIES & SIZES)



CLEAR UTILE MAHOGANY SINGLE RABBETT JAMBS

THICKNESS x WIDTH x LENGTH	DOOR THICKNESS	PAIR
1-1/4" x 6-5/8" x 7'4"	1-3/4"	STOCK
1-1/4" x 6-5/8" x 9'4"	1-3/4"	STOCK

ADDITIONAL SERVICES

Machine frame for 3 hinges and strike	✓
Set up frame only (no door) up to 3/0 x 8/0 (does not include machining, add above)	✓
Rip single rabbet jamb to specified width (includes ease edges)	√
Kerf jambs and change jamb rabbet to 2-1/4" and insert weatherstrip (Available in WHITE and BROWN to 8')	✓
Convert single rabbet jamb to double rabbet from 4-5/8" to 6-5/8" (plow, rip if required, includes ease edges). Please allow 3 days.	✓

CUSTOM DOOR JAMBS



Single Rabbet, Double Rabbet Flat Jambs & Special Profile

We manufacture our own custom profile and size jambs with our in-house moulder. All wood species are available.

CALL FOR PRICING.

Most common species are white oak, red oak, maple cherry, fir and utile mahogany.

Use **CAPTIVA BUILD** for pricing.





PINE JAMBS

PINE FLAT JAMBS

THICKNESS x WIDTH x LENGTH	CLEAR PER PAIR	PRIMED & FJ PER PAIR
11/16" x 4-5/8" x 6'8"	STOCK	STOCK
11/16" x 4-7/8" x 7'0"	-	sтоск
11/16" x 6-5/8" x 6'8"	STOCK	STOCK
11/16" x 6-7/8" x 8'0"	-	sтоск

PINE SPLIT JAMBS FOR 1-3/8" DOORS ONLY

THICKNESS x WIDTH x LENGTH	JAMB OPENING SIZE	CLEAR PER PAIR	PRIMED & FJ PER PAIR
11/16" x 3-5/8" x 6'8"	3-3/8" - 4-1/8"	-	STOCK
11/16" x 5-1/8" x 6'8"	4-7/16" - 5-3/16"	STOCK	sтоск
11/16" x 5-1/8" x 7'0"	4-7/16" - 5-3/16"	-	STOCK
11/16" x 6-5/8" x 6'8"	8-7/16" - 9-3/16"	-	STOCK



MULTIPLY PAIR PRICE x 1.50

PINE DOUBLE RABBETT JAMBS

THICKNESS x WIDTH x LENGTH	DOOR THICKNESS	CLEAR PER PAIR	PRIMED & FJ PER PAIR
1-1/4" x 4-11/16" x 6'8"	1-3/8" / 1-3/4"	STOCK	sтоск
1-1/4" x 4-11/16" x 8'0"	1-3/8" / 1-3/4"	-	STOCK
1-1/4" x 4-7/8" x 7'0"	1-3/8" / 1-3/4"	-	STOCK
1-1/4" x 6-5/8" x 6'8"	1-3/8" / 1-3/4"	-	sтоск
1-1/4" x 6-7/8" x 7'0"	1-3/8" / 1-3/4"	STOCK	STOCK
1-1/4" x 6-5/8" x 8'0"	1-3/8" / 1-3/4"	-	sтоск



PINE SINGLE RABBETT JAMBS

THICKNESS x WIDTH x LENGTH	DOOR THICKNESS	CLEAR	PRIMED & FJ
IIIOKNESS X WIDIII X LENOIII	DOOK IIIIOKILISS	OLLAR	PRIMED & 13
1-1/4" x 4-5/8" x 6'8"	1-3/8"	STOCK	STOCK
1-1/4" x 6-5/8" x 7'0"	1-3/8"	sтоск	STOCK
1-1/4" x 4-7/8" x 7'0"	1-3/4"	STOCK	STOCK
1-1/4" x 6-5/8" x 7'0"	1-3/4"	STOCK	STOCK *
1-1/4" x 9-1/4" x 8'0"	1-3/4"	sтоск	STOCK *

* Jamb is kerfed for foam weatherstripping and dadoed for aluminum sill and machined for hinges and lock at standard Masonite specs

Replacement Weatherstripping

	BROWN	WHITE
80"	✓	-
96"	✓	✓

Weatherstrip a kerfed jamb

Kerf jambs, change rabbet to 2-1/4", insert weatherstripping

* Available 20 Min. fire rated (add to weatherstrip & kert)	✓	
Add for FrameSaver jamb	✓ pr	

^{**} TO BE DISCONTINUED



ASTRAGALS WOOD T-ASTRAGALS



CODE	DESCRIPTION / SIZE	CLEAR	PRIMED
TAST138	1-3/8" x 7'1"	STOCK	sтоск
TAST138P	1-3/4" x 7'1"	sтоск	-
TASTWS	1-3/4" x 7'1" weatherstripped	sтоск	-
TAST8	1-3/4" x 8'1"	sтоск	-

T-ASTRAGALS

CODE	DESCRIPTION	CLEAR
EDFAST8	Fir 1-3/4" x 8-0 RV 1308 Kerfed For Weatherstripping	sтоск
EDPAST8	Pine 1-3/4" x 8-0 RV 1308 Kerfed For Weatherstripping	sтоск
NANSAPAST	Utile Mahogany N-57APD Non-Kerfed Astragal (per LF)	sтоск
NANSAPASTK	Utile Mahogany N-57APD Kerfed For Weatherstripping (per LF)	sтоск

FLAT ASTRAGALS

CODE	DESCRIPTION	CLEAR
FLAST-AFR-MAH-90	African Mahogany 3/8 x 1-1/2" x 9' Flat Astragal	sтоск
FLAST-OAK-70	Oak 3/8 x 1-1/2" x 7' Flat Astragal	sтоск
FLAST-OAK-90	Oak 3/8 x 1-1/2" x 9' Flat Astragal	sтоск
FLAST-MAPLE-70	White Maple 3/8 x 1-1/2" x 7' Flat Astragal	sтоск
FLAST-MAPLE-90	White Maple 3/8 x 1-1/2" x 9' Flat Astragal	sтоск
FLAST-CHERRY-70	Cherry 3/8 x 1-1/2" x 7' Flat Astragal	sтоск
FLAST-CHERRY-90	Cherry 3/8 x 1-1/2" x 9' Flat Astragal	sтоск

ENDURA ULTIMATE ASTRAGALS

CODE	DESCRIPTION	COLOR	HANDING	
ULTAST68E	Ultimate Astragal 6/8 with Thermal Break	White	-	sтоск
ULTAST68BE	Ultimate Astragal 6/8 with Thermal Break	Bronze	-	sтоск
TAST68MPWL	Astragal 6/8 Multipoint with Thermal Break	White	LH	sтоск
TAST68MPWR	Astragal 6/8 Multipoint with Thermal Break	White	RH	sтоск
TAST68MPBL	Astragal 6/8 Multipoint with Thermal Break	Bronze	LH	sтоск
TAST68MPBR	Astragal 6/8 Multipoint with Thermal Break	Bronze	RH	sтоск
ULTASTLT68	Ultimate Lite Astragal 6/8 no Thermal Break	Aluminum	-	sтоск
ULTAST70E	Ultimate Astragal 7/0 with Thermal Break	White	-	sтоск
TAST80MPWL	Astragal 8/0 Multipoint Lock with Thermal Break	White	LH	sтоск
TAST80MPWR	Astragal 8/0 Multipoint Lock with Thermal Break	White	RH	sтоск
ULTASTLT68FLLW	Ultimate Astragal 6/8 with Flip Lever	White	LH	sтоск
ULTASTLT68FLRW	Ultimate Astragal 6/8 with Flip Lever	White	RH	sтоск
ULTASTLT68FLLB	Ultimate Astragal 6/8 with Flip Lever	Bronze	-	sтоск
ULTASTLT68FLRB	Ultimate Astragal 6/8 with Flip Lever	Bronze	-	sтоск
ULTASTHDWRPACKE	Hardware Pack for Ultimate Astragal Replacement	-	-	sтоск

Endura ultimate metal astragals are available in white, bronze and wood grain with various functions, call for pricing.



WOOD THRESHOLDS / SILLS

INTERIOR OAK THRESHOLDS / SADDLES

THICKNESS x LENGTH	3-1/2"	4-1/2"	5-1/2"	6-1/2"	PROFILE NO.
3/4" x 37"	sтоск	sтоск	STOCK	sтоск	N-3812
3/4" x 73"	sтоск	s тоск	sтоск	sтоск	N-3812
THICKNESS x LENGTH	4-11/16"	6-5/8"			PROFILE NO.
1-1/16" x 37"	ѕтоск	STOCK			N-3345
1-1/16" x 73"	sтоск	sтоск			N-3345



EXTERIOR INSWING SILLS

THICKNESS	DOOR THICKNESS	NET SIZE	38"	49"	100"	PROFILE NO.
2 x 8 Red Oak	1-3/4"	1-5/8" x 7-1/4"	STOCK	sтоск	sтоск	N-1165
2 x 10 Red Oak	1-3/4"	1-5/8" x 9-1/4"	STOCK	sтоск	STOCK	N-1165
2 x 10 White Oak	1-3/4"	1-11/16" x 9-1/4"	-	sтоск	-	N-1165
2 x 10 Sapele Mahogany *	1-3/4"	1-5/8" x 9-1/4"	-	STOCK	STOCK	N-1165
2 x 10 Sapele Mahogany	2-1/4"	1-5/8" x 9-1/4"	-	STOCK	STOCK	N-1227



EXTERIOR OUTSWING SILLS

THICKNESS	DOOR THICKNESS	NET SIZE	49"	100"	PROFILE NO.
2 x 8 Oak	1-3/4"	1-5/8" x 7"	sтоск	sтоск	N-920
2 x 10 Oak	1-3/4"	1-5/8" x 9	STOCK	sтоск	N-919



NANTUCKET SERIES

EXTERIOR INSWING SILLS

THICKNESS x WIDTH	DOOR THICKNESS	NET SIZE	49"	100"	PROFILE NO.	
2-1/8 x 9" Sapele Mahogany*	1-3/4"	2-3/16" x 9"	sтоск	STOCK	N-964	
2-1/8 x 9" Sapele Mahogany	2-1/4"	2-3/16" x 9"	STOCK	sтоск	N-2086	



EXTERIOR OUTSWING SILLS

THICKNESS x WIDTH	DOOR THICKNESS	NET SIZE	49"	100"	PROFILE NO.	
1-5/8 x 7-1/4" Sapele Mahogany*	1-3/4"	1-5/8" x 7"	sтоск	STOCK	N-920	
1-5/8 x 9-1/4" Sapele Mahogany	1-3/4"	1-5/8" x 9"	sтоск	sтоск	N-919	



^{*} Sill may be field modified by customer for narrower wall sizes.

OAK, SAPELE & MAHOGANY SILLS ARE NOT WARRANTIED I ALL SILLS ARE SOLID, NOT GLUED UP


^{*} Sills may be field modified by customer for narrower wall sizes.



CAPTIVA FIRE-RATED DOOR CORE


20-MINUTE FIRE-RATED DOOR CROSS SECTION

The fire core is installed between the panels, offering real stile and rail door construction. Intumescent edging goes around the fire core. During a fire, this edging expands to seal the room.



45-60-90-MINUTE FIRE-RATED DOOR **CROSS SECTION**

The door faces surrounding the core are built using actual panel, stile, and rail components to match the profiles of 20 minute and non-rated doors. Intumescent edging goes around the fire core. During a fire, this edging expands to seal the room.



Intumescent edging

CAPTIVA FIRE-RATED WOOD DOORS

RATING	MAXIMUM DOOR SIZE	MINIMUM DOOR THICKNESS	LISTING CATEGORY	MAX GLASS AREA (SQ IN)*	
20 MINUTE	4/0 x 8/0 Single 7/0 x 8/0 Pair	1-3/4"	Category A, Category B Nuetral pressure	1,296	
45 MINUTE	4/0 x 8/0 Single 7/0 x 8/0 Pair	1-3/4"	Category A, Category B	1,296	
60 MINUTE	4/0 x 8/0 Single 7/0 x 8/0 Pair	1-3/4"	Category A, Category B	100†	
90 MINUTE	4/0 × 8/0		Category A, Category B	100†	

^{*} Glass must not be within 5" of edge or opening (bore) or be in a panel † For 60 and 90 minute, glass must be in a metal frame.

FIRE-RATED WOOD JAMBS

RATING	MAXIMUM DOOR SIZE
20 MINUTE	4/0 x 8/0 Single 7/0 x 8/0 Pair
45 MINUTE	4/0 x 8/0 Single 7/0 x 8/0 Pair
60 MINUTE	4/0 x 8/0 Single 7/0 x 8/0 Pair
90 MINUTE	4/0 x 8/0 Single

Metal jambs are also available for all single door applications and double door applications.

Captiva's fire-rated frames are available in 20-45-60-90 minute ratings. This innovative frame system helps ease the installation process through the use of adjustable metal clips, which provide additional strength while avoiding any exposed fasteners. This frame system also allows for easy removal and re-installation without damaging the finished frame. Intumescent edging is built into the jamb. During a fire, this edging expands to seal the room.



Intumescent edging

Double Rabbet, 90-Minute, with Clips (clip removed and clips attached)



Single Rabbet, 60-Minute



Single Rabbet, 90-Minute



Double Rabbet, 60-Minute



Double Rabbet, 90-Minute



CAPTIVA FIRE-RATED DOORS & FRAMES



ARCHITECTURAL CONSISTENCY

Whether residential or commercial applications, Captiva fire-rated doors allow you to seamlessly match the Captiva non-rated doors throughout your project. All of our hundreds of panel door designs and many glass door designs (some restrictions on size) are available fire-rated.

FIRE-RATED WOOD DOOR FRAMES

Our fire-rated wood door frames allow builders and architects to comply with the strictest building code requirements without sacrificing the design integrity of the project. A fire-resistant core is wrapped with wood veneers to perfectly match the non-rated door frames throughout the project. Our fire-rated door frames are available in the wood species of your choice in stain grade, paint grade and prefinished. Our frames come standard with a patented adjustable clip system for fast and simple installation.

MADE IN THE USA

All Captiva Wood Doors are engineered and handcrafted to order at our manufacturing facility in Somerset, MA. When you choose a Captiva Wood Door, not only are you guaranteed a handmade door that will add beauty to your home for years to come, you are also helping to employ local craftsmen and artisans.

FAST LEAD TIMES

Fire-rated doors and frames delivered to you in 2-3 weeks from approved shop drawings.

TECHNICAL SPECIFICATIONS

RATINGS

20, 45, 60, and 90 minute positive pressure door and jamb ratings available

WOOD SPECIES

Available in stain grade, paint grade, and prefinished

WOOD JAMBS

Fire-rated single rabbet, double rabbet, or communicator frame available

THICKNESS

1-3/4" and 2-1/4" door thicknesses available

METAL JAMBS

Available for all ratings

PANELS/PROFILES

Available with flat or raised panels, and all sticking and panel profile designs

DESIGN OPTIONS

All Captiva panel door designs and many glass door designs (some restrictions on glass size)

CUSTOM DESIGNS

Endless styles to meet your needs and perfect for unique designs or historical reproduction

CERTIFICATION

Warnock Hersey label, certified through Intertek testing service

APPLICABLE STANDARDS

ASTM E-152-81a, UL10(c)(1998), UBC 7-2(1997), UL10(b)(1997) NFPA 252(1999), ASTM E-2074(2000), CAN/ULC S104 1980 (R1985)



1255B Grand Army Highway, Somerset, MA 02726 Phone 800-899-4533

2049 Silas Deane Highway, Suite 1A, Rocky Hill, CT 06067 PHONE 800-486-7600

120 Defreest Drive, Suite 19 (Rensselaer Technology Park), Troy, NY 12180
PHONE 800-350-0448

WHOLESALE DOORS

220 Forbes Road, Suite 403, Braintree, MA 02184
PHONE 800-225-4252

For our complete product offering and services, please visit our website:

WWW.CLEARYMILLWORK.COM





CLEARY MILLWORK'S ADVANCED ECOMMERCE WEBSITE

Order doors, millwork, stairparts and more on www.Cleary365.com